

A/

03/30/98
Jc447 U.S. PTO

LERNER AND GREENBERG, P.A.
PATENT ATTORNEYS AND ATTORNEYS AT LAW

2200 Hollywood Boulevard
Hollywood, Florida 33020
Tel: (954) 925-1100
Fax: (954) 925-1101
Telex: 271162 CANTATA
Internet:
Patents@patentusa.com

Herbert L. Lerner (NY Bar)
Laurence A. Greenberg (FL Bar)

Adam A. Jorgensen (Pat. Agent)
Werner H. Stemer (Pat. Agent)
Otto S. Kauder (Pat. Agent)


Mailing Address:
Post Office Box 2480
Hollywood, FL 33022-2480

New York Office
153 E 57th Street
Suite 15G
New York, NY 10022
Tel: (212) 753-7124

"Express Mail" mailing label number **EM405383501US**
Date of Deposit **March 30, 1998**

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Docket No.: GR 95 P 3487


XIOMARA D. JUNCO

Date: March 30, 1998

Hon. Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Enclosed herewith are the necessary papers for filing the following application for Letters Patent:

Applicant : ANWER PUTHAWALA ET AL.

Title : APPARATUS FOR ADMITTING GAS INTO THE PRIMARY COOLANT OF A PRESSURIZED WATER REACTOR

1 sheets of formal drawings in triplicate.

A check in the amount of \$790.00 covering the filing fee.

Information Disclosure Statement and 6 References.

PCT Publication (cover sheet only).

- This application is being filed without a signed oath or declaration under the provisions of 37 CFR 1.53(d). Applicants await notification of the date by which the oath or declaration and the surcharge are due, pursuant to this rule.

The Patent and Trademark Office is hereby given authority to charge Deposit Account No. 12-1099 of Herbert L. Lerner for any fees due or deficiencies of payments made for any purpose during the pendency of the above-identified application.

Respectfully submitted,



For Applicants

LAG:tg

WERNER H. STEMER
REG. NO. 34,956

09050651 033099

APPARATUS FOR ADMITTING GAS INTO THE PRIMARY COOLANT
OF A PRESSURIZED WATER REACTOR

5

Cross-Reference to Related Application:

This application is a continuation of International Application Serial No. PCT/EP96/04057, filed September 16, 1996, which designated the United States.

10

Background of the Invention:

Field of the Invention:

The invention relates to an apparatus for admitting gas into the liquid primary coolant of a pressurized water reactor with hydrogen, wherein the pressurized water reactor is equipped with a volume equalization vessel and with at least one high-pressure pump disposed downstream.

A volume regulating system for the primary coolant of a pressurized water reactor is described in the book entitled VGB-Kernkraftwerks-Seminar 1970 (VGB Nuclear Power Plant Seminar 1970), especially on page 41. That system, through which some of the primary coolant constantly flows, also includes an apparatus for hydrogenation. The goal is to counteract radiolytic decomposition of the coolant in a central region of the nuclear reactor. In that known gas admission apparatus, the hydrogen is admitted into a volume

equalization vessel that is part of the volume regulating system. It is present there in form of a gas cushion above the surface of the liquid. The hydrogen partial pressure in the gas cushion is adjusted in accordance with the desired
5 hydrogen concentration in the primary coolant.

The disadvantage of that gas admission apparatus is that if the volume equalization vessel should leak, hydrogen will escape, which can lead to the development of oxyhydrogen gas
10 with the risk of explosion. An attempt is therefore made to avoid hydrogen-filled gas spaces which are widespread in reactor technology, or at least to keep them as small as possible. Another disadvantage of that gas admission apparatus is that deviations in the hydrogen concentration of
15 the primary coolant can only be reversed slowly, as compared with the hydrogen partial pressure prevailing in the gas cushion.

A further refinement of the aforementioned gas admission
20 apparatus is known from German Published, Non-Prosecuted Patent Application DE 28 28 153, corresponding to US Patents Nos. 4,374,083 and 4,410,486. The hydrogenation of the primary coolant is performed there in a bypass line that is parallel to the volume equalization vessel. A mixer and a gas
25 separator are located downstream of the hydrogen admission point in that bypass line, which discharges into the suction line between the volume equalization vessel and three high-

pressure pumps that operate in parallel. A hydrogen admission line with a control valve that is controlled by a control device leads to the admission point. The control device is supplied, in a manner which is not described in further
5 detail, with the values for the hydrogen content of the coolant and for the operating state of the gas separator.

The disadvantage of that gas admission apparatus is that the hydrogen content of the primary coolant cannot be adjusted
10 exactly. That is because the primary coolant, which is hydrogenated with gas in the bypass line, comes into contact in the suction line with primary coolant of a different hydrogen concentration arriving from the volume equalization vessel and is mixed with it. Moreover, in the aforedescribed
15 control concept there is necessarily a certain amount of gaseous hydrogen in the gas separator. The control concept is relatively complicated, and adjusting the hydrogen concentration takes a comparatively long time. The control device is moreover fairly expensive.

20 German Patent of Addition DE 29 48 297 C2 to the above-mentioned German Published, Non-Prosecuted Patent Application DE 28 28 153, corresponding to US Patents Nos. 4,374,083 and 4,410,486, develops the above-described gas admission
25 apparatus further by providing that the hydrogen is conveyed in a liquid jet compressor, which uses the primary coolant as

its liquid. That version, too, is burdened by the above-described disadvantages.

In a gas admission system which is known from French Patent Application 2 407 554, corresponding to US Patent No. 4,282,062, hydrogen is admitted directly into a high-pressure pump, for the sake of especially high precision in adjusting the hydrogen content.

10 Summary of the Invention:

It is accordingly an object of the invention to provide an apparatus for admitting gas into the primary coolant of a pressurized water reactor, which overcomes the hereinafore-mentioned disadvantages of the heretofore-known devices of this general type, in which a quantity of hydrogen located outside a volume of liquid in a volume equalization vessel can be kept as small as possible and in which fast and exact adjustment of a hydrogen content in the coolant is assured in a relatively simple way.

20

With the foregoing and other objects in view there is provided, in accordance with the invention, in a pressurized water reactor optionally having a volume equalization vessel and at least one high-pressure pump for liquid primary coolant, an apparatus for admitting gas into the liquid primary coolant with hydrogen, comprising a suction line leading to the at least one high-pressure pump; an admission

point for feeding the hydrogen into the suction line; a hydrogen admission line leading to the admission point; a control device having an inlet side and an outlet side; a pressure line connected to the high-pressure pump; a measurement line branching off from the pressure line downstream of the at least one high-pressure pump; a measuring device incorporated into the measurement line and connected to the inlet side of the control device for measuring hydrogen concentration; and a control valve disposed in the hydrogen admission line and connected to the outlet side of the control device.

In accordance with another feature of the invention, the measurement line communicates with the volume equalization vessel or with a dewatering system and is provided on the pressure side of the high-pressure pump. The device for measuring the hydrogen content in the coolant is incorporated into the measurement line. Since the rate of coolant extracted for measurement purposes from the pressure side of the high-pressure pump or high-pressure pumps, which is typically 5 to 15 liters per hour, is relatively slight, it is possible for this measurement line to communicate with the dewatering system of the nuclear reactor, as mentioned above.

In accordance with again another feature of the invention, the at least one high-pressure pump admits the primary coolant extracted from a coolant loop back into the coolant loop.

The apparatus according to the invention offers the advantage of permitting the hydrogen content in the coolant to be adjusted quickly and exactly. Idle spaces for hydrogen are
5 reduced to a minimum. No gas separator is required.

As noted, the apparatus is connected to a control device for triggering the aforementioned control valve. In accordance with a further feature of the invention, the control valve is
10 connected between a hydrogen supply and the admission point. This permits automatic operation of the hydrogen admission into the coolant.

In accordance with an added feature of the invention, there is
15 provided a mixer downstream of the admission point. Since the premixing already takes place in the low-pressure portion, practically only dissolved hydrogen is present in the high-pressure portion.

20 In accordance with an additional feature of the invention, there is provided a bypass line assigned to the volume equalization vessel. As a result, the volume equalization vessel and thus the gas space in it can be kept small.

25 In accordance with yet another feature of the invention, the bypass line discharges upstream of the admission point into the suction line disposed between the volume equalization

vessel and the high-pressure pump. As a result, all of the coolant delivered to the high-pressure pump is brought to essentially a uniform hydrogen content.

- 5 In accordance with a concomitant feature of the invention, the control device is a proportional controller.

Other features which are considered as characteristic for the invention are set forth in the appended claims.

10

- Although the invention is illustrated and described herein as embodied in an apparatus for admitting gas into the primary coolant of a pressurized water reactor, it is nevertheless not intended to be limited to the details shown, since various
15 modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

- The construction and method of operation of the invention,
20 however, together with additional objects and advantages thereof will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

25 Brief Description of the Drawing:

The figure of the drawing is a schematic circuit diagram of an embodiment of an apparatus according to the invention.

Description of the Preferred Embodiments:

Referring now in detail to the single figure of the drawing, there is seen an apparatus for admitting gas into the primary
5 coolant of a pressurized water reactor. A line train 2 that branches off from a non-illustrated primary cooling loop of the pressurized water reactor leads through a manual control valve or a fixture 4 and a flow rate meter 5 into a lower portion of a volume equalization vessel 6. The volume

10 equalization vessel 6 has a lower region 8 which is filled with a primary coolant, such as water (H₂O). A gas space 10 disposed above the primary coolant in the volume equalization vessel 6 communicates through line trains 12, 14 with a non-illustrated exhaust gas system and through a supply line 16
15 with a nitrogen connection. The line train 12 contains a check valve 15, a control valve 17, a flow rate meter 18 and a fixture 20. They are components of a throughput regulating system for nitrogen that is known per se (see German Published, Non-Prosecuted Patent Application DE 28 28 153,
20 corresponding to US Patents Nos. 4,374,083 and 4,410,486).

The line train 14 contains a control valve 22 and a fixture 24. They are components of a pressure regulating system for nitrogen and possibly-present hydrogen that is known per se (see German Published, Non-Prosecuted Patent Application DE 28
25 28 153, corresponding to US Patents Nos. 4,374,083 and 4,410,486). The gas space 10 is substantially filled with

nitrogen (N_2). Nitrogen (N_2) can be delivered through the supply line 16 and a valve 26 as well as a check valve 27.

A bypass line 28 which is parallel to the volume equalization vessel 6 has a control valve 30. The bypass line 28 leads from the line train 2 to a suction line 32 connected at the bottom. The flow rate can be adjusted by a motor, using the control valve 30. A boron concentration replenishment is carried out in the volume equalization vessel 6 with the aid of the control valve 30 and the fixture 4. The boron delivery takes place at an inlet to the line 2 and is not shown in further detail. A certain flow rate is diverted continuously from the main stream through the fixture 4 and is carried into the volume equalization vessel 6, where after mixing with the contents thereof it is carried out again at the bottom through the line 32.

A static mixer 34 is provided in the suction line 32, downstream of the location where the bypass line 28 discharges into it. The static mixer 34 is used for mixing in H_2 . A hydrogen admission or feed line 36 discharges into the suction line 32 at an admission or feed point 38 upstream of the mixer 34. The line 36 may also discharge into the mixer 34. The hydrogen admission line 36 has a check valve 40, a motor-actuable adjusting device or control valve 42, a flow rate meter 44 and a hydrogen supply 48 that can be shut off through the use of a shutoff valve 46. The control valve 42

communicates over a trigger line 50 with a controller or control device 52 having an adjustable desired or set point value transducer 54. This is where the desired value for the desired hydrogen content can be set. The control device 52
5 communicates over a measurement line 56 with a measuring device 58 for hydrogen (H_2). This H_2 measuring device 58 may especially be a measuring device of the kind sold by Orbisphere Laboratories, CH-2000 Neuchatel, Switzerland.

10 Two high-pressure pumps 60, 62 which are provided downstream of the mixer 34, in parallel segments, have respective venting fixtures 64a, 64b and 66a, 66b, between which respective gas measuring devices 65 and 67 are disposed for ascertaining whether or not gas is present in the respective lines. If gas
15 is detected, then the respective outer fixture 64b, 66b is opened and the inner fixture 64a, 66a is closed, so that the gas can escape. The pumps 60, 62 are incorporated between a first and a second valve 68 and 70 on one hand, and a third and a fourth valve 72 and 74 on the other hand. The high-
20 pressure pumps 60, 62 for the most part return the primary coolant from the bypass line 28 back to the primary coolant loop, through a common pressure line 76, a flow rate meter 78 and a valve 80.

25 The disposition of the volume equalization vessel 6 has the following purposes: First, it assures an equalization of fluctuations in the level of primary coolant on the suction

side of the high-pressure pumps 60, 62. Second, it assures a coolant reserve (of 12.5 cbm, for example), if any non-illustrated fixture located upstream of the control valve 30 should by mistake block or interrupt the delivery of primary coolant to the high-pressure pumps 60, 62. These pumps 60, 62 must continue running at all times, for safety reasons.

A measurement or branch line 82 branches off from the pressure line. This measurement line 82 contains the following elements in succession: valves 84, 86, a flow rate meter 88, the measuring device 58 for on-line measurement of the hydrogen content in the primary coolant, a throttle device 90 and a check valve 92. The measurement line 82 then leads into the lower portion 8 of the volume equalization vessel 6. As an alternative, it may also extend into the gas space 10, or into a dewatering system 94. This latter alternative is indicated by dashed line 82a in the drawing. Branches 96, 98 are also provided at the measuring device 58 for determining the dissolved hydrogen. These branches 96, 98 serve to recalibrate the measuring device 58 after a certain length of time in operation (with the aid of a non-illustrated hydrogen container), or to dewater or vent the measurement line 82 as needed.

Only a relatively low rate of coolant is diverted out of the pressure line 76 through the measurement line 82, such as 5 to 10 liters per hour. The diverted coolant is either fed back

into the coolant course through the volume equalization vessel 6, or diverted into the dewatering system 94.

The functional mode of the illustrated apparatus is as

5 follows:

The adjustment of the hydrogenation into the primary coolant is carried out through the control valve 42, which is triggered by the control device 52, on the low-pressure side
10 of the two high-pressure pumps 60, 62, that is to their suction side. The hydrogen admission takes place at the admission point 38. The controlled variable, namely the hydrogen content in the primary coolant (such as water), is conversely measured continuously on the pressure side of the
15 two high-pressure pumps 60, 62 through the use of the measuring device 58 in the measurement line 82. The control device 58 has the task of keeping the hydrogen concentration in the primary coolant at the specified desired value, which may amount to 2.5 ppm, for example.

20

The apparatus shown in the drawing enables unequivocal gas admission, i.e. the establishment of a defined hydrogen concentration in the coolant (water). It is distinguished by a simple structure. Unnecessary gas spaces are avoided.

We claim:

1. In a pressurized water reactor having at least one high-pressure pump for liquid primary coolant, an apparatus for admitting gas into the liquid primary coolant with hydrogen, comprising:
 - a) a suction line leading to the at least one high-pressure pump;
 - b) an admission point for feeding the hydrogen into said suction line;
 - c) a hydrogen admission line leading to said admission point;
 - d) a control device having an inlet side and an outlet side;
 - e) a pressure line connected to the high-pressure pump;
 - f) a measurement line branching off from said pressure line downstream of the at least one high-pressure pump;
 - g) a measuring device incorporated into said measurement line and connected to said inlet side of said control device for measuring hydrogen concentration; and

h) a control valve disposed in said hydrogen admission line and connected to said outlet side of said control device.

2. The apparatus according to claim 1, including a volume equalization vessel, said measurement line leading into said volume equalization vessel.

3. The apparatus according to claim 1, including a dewatering system, said measurement line leading into said dewatering system.

4. The apparatus according to claim 1, wherein the at least one high-pressure pump admits the primary coolant extracted from a coolant loop back into the coolant loop.

5. The apparatus according to claim 1, including a hydrogen supply, said control valve disposed in said hydrogen admission line between said hydrogen supply and said admission point.

6. The apparatus according to claim 1, including a mixer disposed in said suction line.


7. The apparatus according to claim 6, wherein said mixer is disposed downstream of said admission point.


8. The apparatus according to claim 1, including a volume equalization vessel, and a bypass line associated with said volume equalization vessel and having a valve.
9. The apparatus according to claim 8, wherein said bypass line discharges upstream of said admission point into said suction line between said volume equalization vessel and the at least one high-pressure pump.
10. The apparatus according to claim 1, wherein said control device is a proportional controller.


Abstract of the Disclosure:

An apparatus admits gas into the primary coolant of a
pressurized water nuclear reactor having a coolant loop for a
5 liquid coolant, in particular water, to which hydrogen is to
be added. The coolant loop preferably includes a volume
equalization vessel for the coolant as well as at least one
high-pressure pump which admits coolant that has been
extracted from the coolant loop back into the coolant loop
10 again. An admission point for the hydrogen is located in a
suction line on the suction side of the high-pressure pump. A
measurement line on the pressure side of the high-pressure
pump communicates with the volume equalization vessel or with
a dewatering system. A device for measuring the hydrogen
15 content in the coolant is incorporated into the measurement
line. The measuring device is connected through a control
device to a control valve, with which the delivery of hydrogen
to the admission point can be controlled. The gas admission
apparatus assures an unequivocal, precisely maintained
20 hydrogen content in the coolant.

25 LAG/tg







Docket No.: GR 95 P 3487

**COMBINED DECLARATION AND POWER OF ATTORNEY
IN ORIGINAL APPLICATION**

As a below named inventor, I hereby declare that: my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**APPARATUS FOR ADMITTING GAS INTO THE PRIMARY COOLANT
OF A PRESSURIZED WATER REACTOR**

described and claimed in the specification bearing that title, that I understand the content of the specification, that I do not know and do not believe the same was ever known or used in the United States of America before my or our invention thereof, or patented or described in any printed publication in any country before my or our invention thereof or more than one year prior to this application, that the same was not in public use or on sale in the United States of America more than one year prior to this application, that the invention has not been patented or made the subject of an inventor's certificate issued before the date of this application in any country foreign to the United States of America on an application filed by me or my legal representatives or assigns more than twelve month prior to this application, that I acknowledge my duty to disclose information of which I am aware which is material to the examination of this application under 37 C.F.R. 1.56a, and that no application for patent or inventor's certificate of this invention has been filed earlier than the following in any country foreign to the United States prior to this application by me or my legal representatives or assigns:

German Application Serial No. 195 36 450.3, filed September 29, 1995, the International Priority of which is claimed under 35 U.S.C. §119; and International Application Serial No. PCT/EP96/04057, filed September 16, 1996, the Priority of which is claimed under 35 U.S.C. §120.

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

HERBERT L. LERNER (Reg.No.20,435)
LAURENCE A. GREENBERG (Reg.No.29,308)
WERNER H. STEMER (Reg.No.34,956)

Address all correspondence and telephone calls to:

LERNER AND GREENBERG, P.A.
POST OFFICE BOX 2480
HOLLYWOOD, FLORIDA 33022-2480
Tel: (954) 925-1100 - Fax: (954) 925-1101

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

FULL NAME OF FIRST JOINT INVENTOR: ANWER PUTHAWALA

INVENTOR'S SIGNATURE: _____

DATE: _____

Residence: BUCKENHOF, GERMANY

Country of Citizenship: GERMANY

Post Office Address: WEISELSTRASSE 46
D-91054 BUCKENHOF
GERMANY

FULL NAME OF SECOND JOINT INVENTOR: HELMUT STÜNKEL

INVENTOR'S SIGNATURE: _____

DATE: _____

Residence: ERLANGEN, GERMANY

Country of Citizenship: GERMANY

Post Office Address: BURGBERGSTRASSE 33
D-91054 ERLANGEN
GERMANY